



## TEMPO F 650 PLUS

- 10601000 Black
- 10601001 White
- 10601002 Silver



**type:** fresnel luminaire  
**watt:** 300/500/650  
**beam angle:** 7°-60°  
**net weight:** 4 kg  
**lamp base:** GY9.5  
**throw:** 2-10m

## TEMPO PC 650 PLUS

- 10602000 Black
- 10602001 White
- 10602002 Silver



**type:** pebble-convex luminaire  
**watt:** 300/500/650  
**beam angle:** 7°-58°  
**net weight:** 4.2 kg  
**lamp base:** GY9.5  
**throw:** 2-10m

## SUONO F 650 PLUS

- 10601010 Black
- 10601011 White
- 10601012 Silver



**type:** fresnel luminaire  
**watt:** 300/500/650  
**beam angle:** 7°-60°  
**net weight:** 4,1 kg  
**lamp base:** GY9.5  
**throw:** 2-10m

## SUONO PC 650 PLUS

- 10602010 Black
- 10602011 White
- 10602012 Silver



**type:** pebble-convex luminaire  
**watt:** 300/500/650  
**beam angle:** 7°-58°  
**net weight:** 4,3 kg  
**lamp base:** GY9.5  
**throw:** 2-10m

## ARIA F 1000 PLUS

- 10801000 Black
- 10801001 White
- 10801002 Silver



**type:** fresnel luminaire  
**watt:** 650/1000/1200  
**beam angle:** 10°-56°  
**net weight:** 5,6 kg  
**lamp base:** GX9.5  
**throw:** 2-15m

## ARIA PC 1000 PLUS

- 10802000 Black
- 10802001 White
- 10802002 Silver



**type:** pebble-convex luminaire  
**watt:** 650/1000/1200  
**beam angle:** 8°-60°  
**net weight:** 6 kg  
**lamp base:** GX9.5  
**throw:** 2-17m

## NOTA F 1200 PLUS

- 10851000 Black
- 10851001 White
- 10851002 Silver



**type:** fresnel luminaire  
**watt:** 650/1000/1200  
**beam angle:** 10°-56°  
**net weight:** 5,8 kg  
**lamp base:** GX9.5  
**throw:** 2-15m

## NOTA PC 1200 PLUS

- 10852000 Black
- 10852001 White
- 10852002 Silver



**type:** pebble-convex luminaire  
**watt:** 650/1000/1200  
**beam angle:** 8°-60°  
**net weight:** 6,2 kg  
**lamp base:** GX9.5  
**throw:** 2-17m

## TONO F 2000 PLUS

- 10901000 Black



**type:** fresnel luminaire  
**watt:** 1200/2000/2500  
**beam angle:** 10°-70°  
**net weight:** 9 kg  
**lamp base:** G22 (GY16 on request)  
**throw:** 3-20m

## TONO PC 2000 PLUS

- 10902000 Black



**type:** pebble-convex luminaire  
**watt:** 1200/2000/2500  
**beam angle:** 9°-70°  
**net weight:** 10,3 kg  
**lamp base:** G22 (GY16 on request)  
**throw:** 3-20m

# THEATRICAL

# PROFILES - FOLLOWSPOTS

## SUONO 10/28 PLUS

- 10604020 Black
- 10604021 White
- 10604022 Silver



**type:** double condenser profile  
**watt:** 300/500/650  
**beam angle:** 10°-28°  
**net weight:** 7,5 kg  
**lamp base:** GY9.5  
**throw:** 2-15m

## SUONO 20/40 PLUS

- 10604030 Black
- 10604031 White
- 10604032 Silver



**type:** double condenser profile  
**watt:** 300/500/650  
**beam angle:** 20°-40°  
**net weight:** 7 kg  
**lamp base:** GY9.5  
**throw:** 2-15m

## NOTA 8/22

- 10853020 Black



**type:** double condenser profile  
**watt:** 650/1000/1200  
**beam angle:** 8°-22°  
**net weight:** 14,3 kg  
**lamp base:** GX9.5  
**throw:** 5-25m

## NOTA 18/36

- 10853030 Black



**type:** double condenser profile  
**watt:** 650/1000/1200  
**beam angle:** 18°-36°  
**net weight:** 12,3 kg  
**lamp base:** GX9.5  
**throw:** 5-18m

**NOTA 30/55**

■ 10853040 Black



type: double condenser profile  
 watt: 650/1000/1200  
 beam angle: 30°-55°  
 net weight: 11,9 kg  
 lamp base: GX9.5  
 throw: 5-12m

**TONO 8/22**

■ 10903020 Black



type: double condenser profile  
 watt: 2000  
 beam angle: 8°-22°  
 net weight: 14,7 kg  
 lamp base: GY16  
 throw: 6-30m

**TONO 18/36**

■ 10903030 Black



type: double condenser profile  
 watt: 2000  
 beam angle: 18°-36°  
 net weight: 14 kg  
 lamp base: GY16  
 throw: 6-23m

**CANTO 250 msd**

■ 10207080 Black



type: discharge followspot  
 watt: 250 msd/300 sa  
 beam angle: 10°-28°  
 net weight: 13,6 kg  
 lamp base: GY9.5  
 throw: 2-15m

**CANTO 250 HR MK2**

■ 10257180 Black



type: discharge followspot  
 watt: 250 HR  
 beam angle: 8°-22°  
 net weight: 15,1 kg  
 lamp base: GZY9.5  
 throw: 10-20m

**CANTO 575 msd/msr MK2**

■ 11577180 120V

■ 10577180 230V



type: discharge followspot  
 watt: 575 msd/msr  
 beam angle: 8°-22°  
 net weight: 19,8 kg - ballast 16,5 /28 (120V)  
 lamp base: GX9.5  
 throw: 10-30m

**CANTO 700 msd/msr MK2**

■ 11707180 120V

■ 10707180 230V



type: discharge followspot  
 watt: 700 msd/msr  
 beam angle: 8°-22°  
 net weight: 19,8 kg - ballast 16,5 /28 (120V)  
 lamp base: G22  
 throw: 10-35m

**CANTO 1200 msd/msr MK2**

■ 11857180 120V

■ 10857180 230V



type: discharge followspot  
 watt: 1200 msd/msr  
 beam angle: 8°-22°  
 net weight: 19,8 kg - ballast 16,5 /28 (120V)  
 lamp base: G22  
 throw: 10-40m

**CANTO 1200 TH MK2**

■ 11857170 120V

■ 10857170 230V



type: tungsten-halogen followspot  
 watt: 1000 (120V) - 1200 (230V)  
 beam angle: 8°-22°  
 net weight: 18,0 kg  
 lamp base: G22 (120V) / GX9.5 (230V)  
 throw: 10-20m

**CANTO 2000 TH MK2**

■ 11907170 120V

■ 10907170 230V



type: tungsten-halogen followspot  
 watt: 2000  
 beam angle: 8°-22°  
 net weight: 18,0 kg  
 lamp base: GY16  
 throw: 10-30m

## THEATRICAL

**SCENA 300**

■ 10305060 Black



type: IP55 symmetrical flood  
 watt: 200/300/500  
 net weight: 1,3 kg  
 lamp base: R7s  
 throw: 2-5m

**SCENA 1000**

■ 10805060 Black



type: IP55 symmetrical flood  
 watt: 1000/1250  
 net weight: 3,3 kg  
 lamp base: R7s  
 throw: 2-10m

**RIMA A 500 F / PRO**

F ■ 10506050 Black

■ 10506051 White

■ 10506052 Silver



type: asymmetrical flood  
 watt: 200/300/500  
 net weight: 2,0 kg / 2,6 kg (PRO)  
 lamp base: R7s  
 throw: 2-5m

■ 10516050 Black

■ 10516051 White

PRO ■ 10516052 Silver

**RIMA S 500 F / PRO**

F ■ 10506060 Black

■ 10506061 White

■ 10506062 Silver



type: symmetrical flood  
 watt: 200/300/500  
 net weight: 2,0 kg / 2,6 kg (PRO)  
 lamp base: R7s  
 throw: 2-5m

■ 10516060 Black

■ 10516061 White

PRO ■ 10516062 Silver



**INNO A 1000**

- 10806050 *Black*
- 10806051 *White*
- 10806052 *Silver*



**type:** asymmetrical flood  
**watt:** 650/1000/1250  
**net weight:** 5,3 kg  
**lamp base:** R7s  
**throw:** 2-10m

**INNO S 1000**

- 10806060 *Black*
- 10806061 *White*
- 10806062 *Silver*



**type:** symmetrical flood  
**watt:** 650/1000/1250  
**net weight:** 5,3 kg  
**lamp base:** R7s  
**throw:** 2-10m

**PALCO 56**

- 10308010 *Black*
- 10308110 *Polished*



**type:** par 56 can  
**watt:** 300  
**beam angle:** 24° (spot)  
**net weight:** 1,7 kg  
**lamp base:** GX16D  
**throw:** 2-5m

**PALCO 64**

- 10808010 *Black*
- 10808110 *Polished*



**type:** par 64 can  
**watt:** 1000  
**beam angle:** 43° (spot)  
**net weight:** 1,8 kg  
**lamp base:** GX16D  
**throw:** 2-15m

## ARCHITECTURAL

A full list of track lighting accessories is available on request

**RIMA A 70**

- 10076050 *Black*
- 10076051 *White*
- 10076052 *Silver*



**type:** discharge asymmetrical flood  
**watt:** 70 CDM  
**net weight:** 3,6 kg  
**lamp base:** RX7s  
**throw:** 2-5m

**RIMA S 70**

- 10076060 *Black*
- 10076061 *White*
- 10076062 *Silver*



**type:** discharge symmetrical flood  
**watt:** 70 CDM  
**net weight:** 3,6 kg  
**lamp base:** RX7s  
**throw:** 2-5m

**RIMA A 150**

- 10156050 *Black*
- 10156051 *White*
- 10156052 *Silver*



**type:** discharge asymmetrical flood  
**watt:** 150 CDM  
**net weight:** 3,6 kg  
**lamp base:** RX7s  
**throw:** 2-10m

**RIMA S 150**

- 10156060 *Black*
- 10156061 *White*
- 10156062 *Silver*



**type:** discharge symmetrical flood  
**watt:** 150 CDM  
**net weight:** 3,6 kg  
**lamp base:** RX7s  
**throw:** 2-10m

**SOFFIO F 70**

- 10071080 *Black*
- 10071081 *White*
- 10071082 *Silver*



**type:** discharge fresnel luminaire  
**watt:** 70 CDM  
**beam angle:** 7°-63°  
**net weight:** 5,5 kg  
**lamp base:** G12  
**throw:** 2-10m

**SOFFIO F 150**

- 10151080 *Black*
- 10151081 *White*
- 10151082 *Silver*



**type:** discharge fresnel luminaire  
**watt:** 150 CDM  
**beam angle:** 7°-63°  
**net weight:** 6 kg  
**lamp base:** G12  
**throw:** 2-15m

**SOFFIO 10/28 70W**

- 10073020 *Black*
- 10073021 *White*
- 10073022 *Silver*



**type:** discharge profile  
**watt:** 70 CDM  
**beam angle:** 10°-28°  
**net weight:** 8,5 kg  
**lamp base:** G12  
**throw:** 2-10m

**SOFFIO 10/28 150W**

- 10153020 *Black*
- 10153021 *White*
- 10153022 *Silver*



**type:** discharge profile  
**watt:** 150 CDM  
**beam angle:** 10°-28°  
**net weight:** 9 kg  
**lamp base:** G12  
**throw:** 2-15m

**SOFFIO 20/40 70W**

- 10073030 *Black*
- 10073031 *White*
- 10073032 *Silver*



**type:** discharge profile  
**watt:** 70 CDM  
**beam angle:** 20°-40°  
**net weight:** 8 kg  
**lamp base:** G12  
**throw:** 2-10m

**SOFFIO 20/40 150W**

- 10153030 *Black*
- 10153031 *White*
- 10153032 *Silver*



**type:** discharge profile  
**watt:** 150 CDM  
**beam angle:** 20°-40°  
**net weight:** 8,5 kg  
**lamp base:** G12  
**throw:** 2-15m

**SUONO F 250 msd**

- 10201080 Black
- 10201081 White
- 10201082 Silver



**type:** discharge fresnel luminaire  
**watt:** 250 msd / 300 msa  
**beam angle:** 7°-63°  
**net weight:** 8,6 kg  
**lamp base:** GY9,5  
**throw:** 2-20m

**SUONO D 10/28**

- 10203020 Black
- 10203021 White
- 10203022 Silver



**type:** discharge profile  
**watt:** 250 msd / 300 msa  
**beam angle:** 10°-28°  
**net weight:** 12,4 kg  
**lamp base:** GY9,5  
**throw:** 2-20m

**SUONO D 20/40**

- 10203030 Black
- 10203031 White
- 10203032 Silver



**type:** discharge profile  
**watt:** 250 msd / 300 msa  
**beam angle:** 20°-40°  
**net weight:** 11,8 kg  
**lamp base:** GY9,5  
**throw:** 2-20m

**POLE OPERATED****SOFFIO F 150 P.O.**

- 12151080 Black
- 12151081 White
- 12151082 Silver



**type:** P.O. discharge fresnel  
**watt:** 150 cdm  
**beam angle:** 7°-63°  
**net weight:** 7,8 kg  
**lamp base:** G12  
**throw:** 2-15m

**SUONO F 250 P.O.**

- 12201080 Black
- 12201081 White
- 12201082 Silver



**type:** P.O. discharge fresnel  
**watt:** 250 msd - 300 msa  
**beam angle:** 7°-63°  
**net weight:** 10,4 kg  
**lamp base:** GY9,5  
**throw:** 2-20m

**NOTA F 1200 P.O.**

- 12851000 Black
- 12851001 White
- 12851002 Silver



**type:** P.O. halogen fresnel  
**watt:** 650/1000/1200  
**beam angle:** 10°-56°  
**net weight:** 7,3 kg  
**lamp base:** GX9,5  
**throw:** 2-15m

**TONO F 2000 P.O.**

- 12901000 Black



**type:** P.O. halogen fresnel  
**watt:** 1200/2000/2500  
**beam angle:** 10°-70°  
**net weight:** 10,7 kg  
**lamp base:** G22 (GY16 on request)  
**throw:** 3-20m

**COLOUR SCROLLERS****XPRESS 13**

- 20106013



**standard mounting plate:** 160 x 160 mm  
**front aperture:**  $\varnothing$  135 mm  
**gel string capacity:** 8-11-16-21 frames  
**scroll speed:** min. 1.6 sec. ( 21 frames)  
**Dmx/power input:** XLR 4-pin-dmx  
 512+24V dc  
**net weight:** 2.2 kg **new**

**XPRESS 19**

- 20106019



**standard mounting plate:** 253 x 253 mm  
**front aperture:**  $\varnothing$  195 mm  
**gel string capacity:** 8-11-16-21 frames  
**scroll speed:** min. 1.9 sec. ( 21 frames)  
**Dmx/power input:** XLR 4-pin-dmx  
 512+24V dc  
**net weight:** 2,7 kg **new**

**XPRESS 26**

- 20106026



**standard mounting plate:** 313 x 313 mm  
**front aperture:**  $\varnothing$  270 mm  
**gel string capacity:** 8-11-16-21 frames  
**scroll speed:** min. 3.2 sec. ( 21 frames)  
**Dmx/power input:** XLR 4-pin-dmx  
 512+24V dc  
**net weight:** 3,4 kg **new**

**XPRESS MOVING**

- 10579070



HPL 575 tungsten halogen moving head with Xpress 18 scroller  
**movement:** 540° pan/ 270° tilt, 8/16 bit resol.  
**dimmer:** built-in electronic dimmer 0/100%  
**net weight:** 16,5 kg

**PDU 1**

- 20106020



power distribution unit for 1 scroller  
**power input:** 120/240 volts 50/60 Hz  
**DMX input:** XLR 5-pin  
**DMX output to scroller:** XLR 4-pin/24V  
**net weight:** 1,3 kg

**PDU 6**

- 20106160



power distribution unit for 6 scrollers  
**power input:** 120/240 volts 50/60 Hz  
**DMX input:** XLR 5-pin  
**DMX output to scroller:** XLR 4-pin/24V  
**net weight:** 5,3 kg **new**



PROFESSIONAL LIGHTING PRODUCTS  
designed and made in Italy

Via Berna 14 - Z.I. Bosco dell'Irta  
46042 Castel Goffredo - Mantova - Italy  
**Tel** +39 0376 771777 - **Fax** +39 0376 772140  
**E-mail** info@ldr.it - **Web** www.ldr.it

